



**Features :**

- Use with different bus bar
- Panel mount / Din rail mount (Optional accessory)
- Accuracy : Class 0.5

Cetification :  $\text{C} \text{ } \text{E}$

**Input / Output specifications**

Rated primary rating	800A to 4000A
Rated secondary output	5A

**Technical specifications**

Rated burden	15VA
Class of accuracy	0.5
Thermal Nominal Continuous	120% of In Rated Current (I <sub>th</sub> )
Thermal short circuit current (I <sub>th</sub> )	I <sub>th</sub> = 60 X In for 1 sec
Instrument security factor	FS <5
Isolation class	E (120°C max)
Max operating voltage (U <sub>m</sub> )	720V maximum
Isolation test voltage	3kV AC 1 min
Nominal rated frequency	AC 50Hz - 60Hz


**Environmental specifications**

Ambient temperature	0°C...+50°C
Humidity	< 95% RH (non condensing)
Storage temperature	-5°C...+50°C


Mounting modes	Panel Mount / DIN rail Mount
----------------	------------------------------

**Standard**

Applicable standard	IEC 61869 - 2
---------------------	---------------



**Accessories (DIN Rail Clamp )**



## Ordering Information

PRODUCT CODE	WIRE APERTURE In mm	CURRENT RATIO	BURDEN IN VA	ACCURACY CLASS
SPCT-140/100-800/5A-VA15-CL0.5-CE	100x30	800 / 5	15	0.5
SPCT-140/100-1000/5A-VA15-CL0.5-CE	100x30	1000 / 5	15	0.5
SPCT-140/100-1200/5A-VA15-CL0.5-CE	100x30	1200 / 5	15	0.5
SPCT-140/100-1250/5A-VA15-CL0.5-CE	100x30	1250 / 5	15	0.5
SPCT-140/100-1500/5A-VA15-CL0.5-CE	100x30	1500 / 5	15	0.5
SPCT-140/100-1600/5A-VA15-CL0.5-CE	100x30	1600 / 5	15	0.5
SPCT-140/100-2000/5A-VA15-CL0.5-CE	100x30	2000 / 5	15	0.5
SPCT-140/100-2500/5A-VA15-CL0.5-CE	100x30	2500 / 5	15	0.5
SPCT-140/100-3000/5A-VA15-CL0.5-CE	100x30	3000 / 5	15	0.5
SPCT-140/100-3500/5A-VA15-CL0.5	100x30	3500 / 5	15	0.5
SPCT-140/100-4000/5A-VA15-CL0.5	100x30	4000 / 5	15	0.5

## Accessories

PRODUCT CODE	CERTIFICATION
AC-SPCT-DRAIL-01 (Pack of 10)	---